



Housing Color:



Sanded Black
RAL9005
(BL)



Sanded Dark Grey
RAL7037
(DG)



Sanded White
RAL9003
(WH)

Accessories(Optional):



Honeycomb Louver
HL18 - 25W
HL30 - 30W
HL48 - 48W



Applications:

Staircases, steps, lobby, reception, corridors, pedestrian ramps, walkways, architectural structures, building vicinity, yard, garden etc.



Disclaimer:

LuxeLED All rights reserved. LuxeLED does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by LuxeLED.

Key Information

Shape	Round
Mounting Type	Ceiling mounted
Engine Orientation	Fixed
LED Type	COB LED
Power	25W 30W 48W
CCT(K) Options	3000K 4000K 5000K
Luminous Efficacy	85-95lm/W
CRI	>85
Lifespan	50,000 hours(L70 B30 @35°)

Physical

Housing	Die cast aluminium
Housing Finish	Powder coating T=60~80μm
Housing Color	Sanded Black - 9005 Sanded Dark Grey - 9037 Sanded White - 9003
Lens	Optics Reflector. efficiency≥85%
Diffuser	Tempered glass
Gasket	Tooling shaped seal
Power Cable (Outside of Luminaire)	240VAC: H05RN-F 3x1.0mm ² , L=0.5m 24VDC: H05RN-F 2x1.0mm ² , L=0.5m

Environmental

Installation Environment	Outdoor
IK Rating	06
IP Rating	IP65
Operating Temperature	-20° to 45°C

Electrical

Input Current	220~240VAC 50/60Hz
Standard	On/off
Dimming Options	No

Ordering Guide:

Product	CCT (K)	Wattage (W)	Beam Angle(°)	Body Finish	Driver
BE = Beko	3K=3000K 4K=4000K 5K=5000K	25W 30W 48W	15° 20° 25° 38° 55° 15° 25° 36° 45° 60° 15° 25° 36° 45° 60°	BL = Black WH = White DG = Dark Grey	S=On/Off

* Please choose wattages from same color box matching respective product.

Product Code	Wattage	CCT	Lumens	Dimensions (mm)
BE-3K-25W-15°-WH-S	25W	3000K	2205lm	Ø130mm X 165
BE-3K-30W-15°-WH-S	30W	3000K	2851lm	Ø160mm X 185
BE-3K-48W-15°-WH-S	48W	3000K	4482lm	Ø200mm X 235