



Beam Angles : 30° | 40° | 50° | 60°






Water Proof Solution:



A Water-Stopper(Included)

A IP67 water-stopper is added in the end of luminaires as standard assembly which is also an important system for water resistance.


Sleeve Details:



Note:

Please ensure quick water drainage from in ground luminaire cavity to avoid water accumulation around the luminaire housing.

Porous base layer for easy drainage of water.



Note:

Exposure of luminaire to TSE(Treated Sewage Effluent/ Purple Water) should be eliminated.

Warranty»

The warranty will be void if the specified installation method is not followed.

Key Information

Shape	Linear
Mounting Type	Inground
LED Type	LED SMD Module
Power Options	6W / 12W / 24W / 30W
CCT(K) Options	2700K / 3000K / 4000K / 5000K
Luminous Efficacy	81.6lm/W
CRI	85
SDCM	< 5
Lifespan	50,000 hours(L90 B10 @35°)

Physical

Housing	Extruded aluminium with corrosion
PCB	Excellent heat conductivity aluminum, coefficient of heat Conductivity≥2.0w/mk
Diffuser	Tempered glass . T=8mm
Lens	Optical lens, efficiency≥85%
Gasket	Glass and housing are silicone sealed
Glass Pressure Capacity	3180Kgs
Power Cable	H03VV-F 2x0.75mm ² , L=0.25mm
Cable Gland	IP67 Nickel coated copper
Sleeve Material	Aluminium, Powder coated

Environmental

Installation Environment	Indoor and Outdoor
IK Rating	08
IP Rating	IP67
Operating Temperature	-20° to 50°C

Technical Details

Input Voltage	24VDC
Class Rating	Class I
Standard	On/off
Dimming Options	DALI2 1-10V

Ordering Guide:

Product	CCT (K)	Wattage (W)	Length (mm)	Beam Angle(°)	Driver
ED II = Edge II	2.7K=2700K	6W	255mm	30° 40° 50° 60°	S=On/Off D=DALI2 V=1-10V
	3K=3000K	12W	505mm		
	4K=4000K	24W	1005mm		
	5K=5000K	30W	1255mm		


* Please choose wattage, length and angle from same color box matching respective product.

Product Code	Wattage	CCT	Lumens	Dimensions (mm)
ED I-3K-6W-255mm-120°-S	6W	3000K	490lm	33 x 80 x 260mm
ED I-3K-12W-505mm-120°-S	12W	3000K	900lm	33 x 80 x 510mm
ED I-3K-24W-1005mm-120°-S	24W	3000K	1976lm	33 x 80 x 1010mm
ED I-3K-30W-1255mm-120°-S	30W	3000K	2466lm	33 x 80 x 1260mm


Applications:

Exterior facade walls, building vicinity, walkways and ramps

Application Photo:



Wiring:



Disclaimer:

LuxeLED All rights reserved. LuxeLED does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by LuxeLED.