



Beam Angles: 120°/window - Single Window
80°/window - Twin Windows
40°/window - Quad Windows



Drive-Over >2000Kgs



Single Window (S)

Twin Window (T)

Quad Window (Q)



Paint Finish:



SUS 316(SS)
(Standard)



Sanded Bronze(RAL9038)
(Optional)

Mounting Sleeve(Included):



Water Proof Solution:



A Water-Stopper(Included)

A IP67 water-stopper is added in the end of luminaires as standard assembly which is also an important system for water resistance.

B IP67 Jiffy Quick Plug /Socket Connector(Optional)

A IP67 connector is as an optional assembly and ensures that water vapor will not enter into luminaires directly.



Key Information

Shape	Round
Mounting Type	Inground
LED Type	LED SMD
Power Options	10W
CCT(K) Options	2700K 3000K 4000K 5000K
Luminous Efficacy	20-51lm/W
CRI	85
SDCM	< 3
Lifespan	50,000 hours(L90 B10 @35°)

Physical

Housing	Die cast aluminium dark grey powder coated
Front Cover	Hard chrome-plated stainless steel SUS 316#
Diffuser	UV stop & Fireproof PC
Reflector	Optical Reflector efficiency≥90%
Gasket	Silicon rubber molding shaped seal
Power Cable (Outside of Luminaire)	240VAC: H05RN-F 3x1.0mm ² , L=0.5m 24VDC: H05RN-F 2x1.0mm ² , L=0.5m
Load Capacity	>2000Kgs
Mounting Sleeve Material	PC/ABS alloys

Environmental

Installation Environment	Outdoor
IK Rating	10
IP Rating	IP67
Operating Temperature	-20° to 50°C
Humidity	10~90%

Electrical:

Input Voltage	220~240VAC 50/60Hz 24VDC (as an option)
Standard	On/off
Dimming Options	DALI2 0-10V

Ordering Guide:

Product	CCT (K)	Wattage (W)	Window	Voltage	Color Finish	Driver
COR I = Coral I	2.7K=2700K 3K=3000K 4K=4000K 5K=5000K	10W	S = Single	240VAC	SS = Stainless BR = Bronze	S=On/Off D=DALI2 V=0-10V
			T = Twin	24VDC		
			Q = Four			

* Please choose aperture and voltage from same color box matching respective product.

Product Code	Wattage	CCT	Lumens	Dimensions (mm)
COR I-3K-10W-S-240VAC-SS-S	10W	3000K	205lm	Ø170x 110mm
COR I-3K-10W-T-240VAC-SS-S	10W	3000K	427lm	Ø170x 110mm
COR I-3K-10W-Q-240VAC-SS-S	10W	3000K	505lm	Ø170x 110mm

Applications:

Pathways, entrances, ramps, interior / exterior, accent lighting, shop, hotel, lobby, reception, foyers, corridors and driveways.

Application Photo:

